

Precision Slotting Head

ORDER NO. VSH-125 CODE NO. 1012-010



SLOTING HEAD



← Slotting bar & cutter

Features


- Special design worm and worm gear with linkage transmission mechanism, well construction and highly power output.
- The ram-sliding surface are hardened and precision ground
- Built in lubricating system for smoothly running and prolong the life of head
- Available mounting on any type milling m/c back side of the ram.

Specification

Stroke: 125mm (5")
 No. of stroke speed change: 5 steps
 Stroke speed (stroke/min): 30, 47, 69, 98, 140 spm (50HZ)
 Stroke speed (stroke/min): 35, 54, 79, 112, 160 spm (60HZ)
 Driving Motor: 3/4HP-6P
 WEIGHT: 150kgs



VSH-C: 6 mm, 7 mm, 8 mm, 10 mm



CUTTER SIZE

ORDER NO.	CUTTER & DESCRIPTION	WEIGHT (kg)	CODE NO.
VSH-6C	Slotting bar 6mm	0.56	1012-013
VSH-7C	Slotting bar 7mm	0.62	1012-014
VSH-8C	Slotting bar 8mm	0.80	1012-015
VSH-10C	Slotting bar 10mm	0.81	1012-016
VSH-FGA	FLANGE A	11	1012-017
VSH-FGB	FLANGE B	23	1012-018

Optional Accessories

- Flange A
- Flange B
- Slotting bar & cutter 4, 5, 6, 7, 8, 10mm

