

Face Mill Arbor

NT30, 40, 50, R8, MT3, 4


DIN 2080/ISO SHANK



NT40 WITH
MAHO GAP



NT30



MATERIAL:SCM-21 HARDNESS:HRC 50°-55°

Squareness of mounting surface:Less than 0.0002"(0.005mm)

Deflection in shaft and taper:Less than 0.0002"(0.005mm)

INCH THREAD

INCH FMA TYPE



ORDER NO.	TAPER	SHAFT SIZE				MOUNTING SIZE		WEIGHT (kg)	CODE NO.
		D	H	W	K	C	L		
VF-101	NT30	25.4	20	9.57	5	65	20	0.7	3212-001
VF-102		31.75	23	12.75	7	73	20	1	3212-002
VF-103		38.1	22	15.90	9	82	20	1.1	3212-003
VF-104	NT40	25.4	20	9.57	5	65	20	1.2	3212-004
VF-105		31.75	22	12.75	7	73	20	1.5	3212-005
VF-106		38.1	23	15.90	9	82	20	1.8	3212-006
VF-109	NT50	25.4	20	9.57	5	65	20	3.2	3212-009
VF-110		31.75	22	12.75	7	73	20	3.3	3212-010
VF-111		38.1	23	15.90	9	82	20	3.6	3212-011
VF-112	R8	50.8	24	19.05	10	95	20	4	3212-012
VF-114		25.4	20	9.57	5	40	20	0.9	3212-014
VF-115		31.75	22	12.75	7	53	20	1.2	3212-015
VF-116	MT-3	25.4	20	9.57	5	40	20	0.7	3212-016
VF-117	MT-4	25.4	20	9.57	5	40	20	1	3212-017

METRIC FMB TYPE MM THREAD

ORDER NO.	TAPER	SHAFT SIZE				MOUNTING SIZE		WEIGHT (kg)	CODE NO.
		D	H	W	K	C	L		
VF-120	NT30	22	18	9.57	5	40	20	0.7	3212-100
VF-121		27	20	12.75	7	53	20	0.8	3212-101
VF-122		32	23	15.90	7	63	20	1.1	3212-102
VF-123	NT40	22	18	9.57	5	40	20	1.2	3212-103
VF-123-1		16	17	16.4		40	20	1.17	3212-103A
VF-124		27	20	12.75	7	53	20	1.3	3212-104
VF-125	NT50	32	23	15.90	7	63	20	1.4	3212-105
VF-126		40	26	19.05	8	85	20	1.9	3212-106
VF-127		60	32	25.40	5	128	24	4	3212-107
VF-128	R8	22	18	9.57	5	40	20	3.1	3212-108
VF-129		27	20	12.75	7	53	20	3.3	3212-109
VF-130		32	23	15.90	7	63	20	3.5	3212-110
VF-131	MT3	40	26	19.05	8	85	20	3.7	3212-111
VF-132		60	32	25.40	5	128.57	24	5.4	3212-112
VF-134		22	18	9.57	5	40	20	0.9	3212-113
VF-135	MT4	27	20	12.75	7	53	20	1	3212-114
VF-136		27	20	9.57	7	53	20	0.7	3212-115
VF-137		27	20	9.57	7	53	20	1.1	3212-116

FACE MILL ARBOR