


SK Spring Collet System



HRC:47° 10µm JIS STD. 15000 R.P.M.

A GRADE



SCM 440

THE RUNOUT OF A COLLET IS 10µ.

THE GRIPPING RANGE OF DIA. OVER 3MM IS 0.5MM

THE GRIPPING RANGE OF DIA. BELOW 3MM IS 0.25MM

TYPE WEIGHT (KGS)	SK-16A				SK-20A				SK-25A			
	0.08				0.135				0.205			
	ORDER NO.	ØD	CAP. mm Ø	CODE NO.	ORDER NO.	ØD	CAP. mm Ø	CODE NO.	ORDER NO.	ØD	CAP. mm Ø	CODE NO.
INDIVIDUAL UNIT	SK1601A	3	3-2.75	3218-430	SK2001A	3	3-2.75	3218-460	SK2501A	6	6-5.5	3218-470
	SK1602A	3.175	3.175-2.7	3218-431	SK2002A	4	4-3.5	3218-461	SK2502A	8	8-7.5	3218-471
	SK1603A	3.5	3.5-3	3218-432	SK2003A	6	6-5.5	3218-462	SK2503A	10	10-9.5	3218-472
	SK1604A	4	4-3.5	3218-433	SK2004A	8	8-7.5	3218-463	SK2504A	12	12-11.5	3218-473
	SK1605A	4.5	4.5-4	3218-434	SK2005A	10	10-9.5	3218-464	SK2505A	14	14-13.5	3218-474
	SK1606A	5	5-4.5	3218-435	SK2006A	12	12-11.5	3218-465	SK2506A	16	16-15.5	3218-475
	SK1607A	5.5	5.5-5	3218-436	SK2007A	16	16-15.5	3218-466	SK2507A	18	18-17.5	3218-476
	SK1608A	6	6-5.5	3218-437	SK2008A	20	20-19.5	3218-467	SK2508A	20	20-19.5	3218-477
	SK1609A	6.5	6.5-6	3218-438					SK2509A	22	22-21.5	3218-478
	SK1610A	7	7-6.5	3218-439					SK2510A	24	24-23.5	3218-479
	SK1611A	7.5	7.5-7	3218-440					SK2511A	25	25-24.5	3218-480
	SK1612A	8	8-7.5	3218-441					SK2512A	25.4	25.4-25	3218-481
	SK1613A	8.5	8.5-8	3218-442								
	SK1614A	9	9-8.5	3218-443								
	SK1615A	9.5	9.5-9	3218-444								
	SK1616A	10	10-9.5	3218-445								
	SK1617A	10.5	10.5-10	3218-446								
	SK1618A	11	11-10.5	3218-447								
	SK1619A	11.5	11.5-11	3218-448								
	SK1620A	12	12-11.5	3218-449								
	SK1621A	12.5	12.5-12	3218-450								
	SK1622A	13	13-12.5	3218-451								
	SK1623A	13.5	13.5-13	3218-452								
	SK1624A	14	14-13.5	3218-453								
	SK1625A	14.5	14.5-14	3218-454								
	SK1626A	15	15-14.5	3218-455								
	SK1627A	15.5	15.5-15	3218-456								
	SK1628A	16	16-15.5	3218-457								

SK COLLET