

COPA MANDRIL HIDRAULICA DE 3 MORDAZAS 3-780-0500



Chuck Size	in	5
Spindle Nose		A2-4
Thru Hole	in(mm)	1.299 (33)
Jaw Stroke	in(mm)	0.213 (5.4)
Plunger Stroke	in(mm)	0.394 (10)
Gripping Dia Max	in(mm)	5.315 (135)
Gripping Dia Min	in(mm)	0.394 (10)
Max Pull Force	lbf(kgf)	3806 (1730)
Max Gripping Force	lbf(kgf)	7854 (3570)
Max Speed	RPM	7000
Weight	lb (kg)	13.42 (6.1)

DIAMETRO DE 5" 125MM
MONTAJE PLAIN BACK TYPE B-200
CUERPO EN ACERO, RPM 7000

A	in(mm)	5.315 (135)
B	in(mm)	2.362 (60)
C	in(mm)	4.331 (110)
D	in(mm)	2.501 (63.513)
E	in(mm)	0.787 (20)
F	in(mm)	0.157 (4)
G	in(mm)	3.78 (96)
H1	in(mm)	PCDØ145
I1	in(mm)	3-M8x1.25P
K	in(mm)	3-M10x1.5P
L	in(mm)	0.591 (15)
M		0.551 (14)
N max	in(mm)	1.031 (26.2)
N min	in(mm)	0.925 (23.5)
O max	in(mm)	0.748 (19)
O min	in(mm)	0.236 (6)
P max	in(mm)	0.039 (1)
P min	in(mm)	-0.354 (-9)
H	in(mm)	3.252 (82.6)
Q	in(mm)	0.984 (25)
J	in(mm)	1.299 (33)
R	in(mm)	0.394 (10)
S	in(mm)	0.787 (20)
T	in(mm)	0.079 (2)
U		M40x1.5P
V	in(mm)	0.472 (12)
W	in(mm)	1.24 (31.5)
X	in(mm)	2.441 (62)

